



First 44 Performance



seawapps

CONNECT YOUR BOAT FREE YOUR MIND

GENERAL SPECIFICATIONS

• L.O.A		
- First 44	14,15m	46'5"
- First 44 Performance	14,65m	48'1"
• Hull length	13,17m	43'2"
• L.W.L.	12,82m	42'1"
• Beam	4,25m	13'11"
• Standard draft (Cast iron)	2,15m	7'1"
• Standard ballast weight (Cast iron)	3 300kg	7,275 lbs
• Performance draft (Cast iron/Lead)	2,60m	8'6"
• Performance ballast weight (Cast iron/Lead)	3 000kg	6,612 lbs
• Air draft		
- Aluminum mast version	19,70m	64'8"
- Carbon mast version	21,32m	69'11"
• Light displacement	10 660kg	23,495 lbs
• Fuel capacity (standard)	200L	53 US Gal
• Fresh water capacity		
- First 44 (standard)	370L	98 US Gal
- First 44 (Option)	200L	53 US Gal
• Engine power		
- Sail drive (standard)	57 HP	57 HP

ARCHITECTS / DESIGNERS

- Naval Architect: BISCONTINI YACHT DESIGN
- Outside & interior design: LORENZO ARGENTO

EC CERTIFICATION

- Category A - 12 people (with ballast option: 6 people)
- Category B - 12 people
- Category C - 14 people

STANDARD SAILS DIMENSIONS

CLASSICAL MAST ALUMINUM

• Classic mainsail	53m ²	570 sq/ft
• Genoa		
- Furler below deck	53m ²	570 sq/ft
- Furler under deck	50m ²	539 sq/ft
• Code 0	95m ²	1,022 sq/ft
• Asymmetric spinnaker	170m ²	1,830 sq/ft
• I	16,80m	55'1"
• J -Furler below deck	5,98m	19'7"
• J -Furler under deck	5,60m	18'4"
• P	16,10m	52'10"
• E	5,50m	18'1"

CARBON CLASSICAL MAST (+ 1,60m / 5'3")

• Classic mainsail	61m ²	657 sq/ft
• Genoa		
- Furler below deck	60m ²	646 sq/ft
- Furler under deck	56m ²	603 sq/ft
• Code 0	105m ²	1,130 sq/ft
• Asymmetric spinnaker	207m ²	2,228 sq/ft
• I	18,50m	60'8"
• J -Furler below deck	5,98m	19'7"
• J -Furler under deck	5,60m	18'4"
• P	17,75m	58'3"
• E	5,50m	18'1"

STANDARD EQUIPMENT

CONSTRUCTION

- Design in accordance with European Directive requirements and according to CE certification
- ISO 12215 certified structure
- Balsa sandwich infusion hull
- Vacuum infused structural inner liner (Fabrics - resin) bonded to the hull
- Fiberglass sandwich, PET foam, balsa wood infusion deck, with diamond pattern non-slip coating
- Cast iron keel attached with bolts and bonded stainless steel backplate
- Polyester bowsprit, 1m / 3'3"
- Twin rudders hung with stainless steel stock
- White coloured hull - Aluminum grey hull decoration
- 6 Hull portholes

DECK EQUIPMENT

RIGGING

- **Anodized aluminum classical mast** tapered, deck stepped, 2 Aft swept spreaders, Sparcraft, classic boom (or **Black lacquered aluminum classical mast** tapered, deck stepped, 2 Aft swept spreaders, Sparcraft, Black lacquered boom with LED lighting - warm white)
 - C-strand Rigging,
 - C-strand stainless steel split backstay with manual hydraulic piston to starboard (hydraulic unit optional),
 - Harken Element blocks at foot of mast,
 - Facnor Facsilde FR25 mainsail track (without traveller)
 - 1 mainsail attachment point at bottom of cockpit with 1 stand-up block
 - **Carbon classical mast** tapered, deck-stepped (+ 1,60m / 5'3", Weight saving: 75kg / 165 lbs) 2 Aft swept spreaders, Sparcraft, Black lacquered boom with LED lighting - warm white
 - ROD Standing rigging
 - Textile backstay crow's foot with manual hydraulic piston to starboard
 - Harken Black Magic blocks at mast foot
 - Harken System A mainsail track (without traveller)
 - Mainsail sheets track in the bottom of the cockpit - Harken 1,80 m / 5'11" + track
- Note:** The carbon mast requires a mastjack (both for installation on delivery and for tensioning the shrouds during regattas), equipment not supplied by the yard.
- Black lacquered aluminum rigid kicking strap with Dyneema tackle and friction rings
 - Genoa tracks on the roof with traveller and hauling line controlled from the cockpit
 - Manual Genoa furler on the deck (Facnor Flatdeck)
 - German system (Two-way mainsheet at the helm station)
 - All lines brought back to the helm stations (except boom topping lift)
 - Dyneema Complete running rigging:
 - Mainsheet halyard sheave block,
 - Genoa halyard,
 - Boom uphaul (polyester) with cleat on mast,
 - Mainsheet,
 - 2 Genoa sheets,
 - 2 Automatic reefing system
 - 8 halyard clutches to port, 4 to starboard
 - Harken pulleys
 - 2 Spinnaker sheet chain plates/code 0
 - Running rigging hidden
 - Lazy-jacks
 - 2 Flag halyards

WINCHES (First 44)

- 2 H46.2 STA manual self-tailing manoeuvre winches (at helm stations)
- 2 H50.2 STA manual self-tailing genoa winches (at helm stations)
- 2 Aluminum Speed Grip winch handles

SAILS

- Boast supplied without sail - Available as option

FIRST 44 PERFORMANCE VERSION

(compatible with standard mast, black lacquered aluminium 2 aft swept spreaders mast and carbon mast, compatible with both keels)

- Carbon bowsprit, 1,50m / 4'11" (in lieu of standard)
- Mainsail Cunningham
- Mainsail traveller at bottom of cockpit (instead of single point of attachment)
- 2nd genoa halyard
- Harken Carbo racing dual-groove head foil instead of the flat deck furling system
- 8:1 barber hauler
- DOWNWIND Pack (2 Harken Black Magic blocks for spinnaker/code 0 sheet, 1 Harken Black Magic block for spinnaker tack led back to the dedicated cleat in the cockpit, Dyneema halyard sheave with block for spinnaker or code 0, 1 Dyneema halyard for spinnaker, Barber hauler with blocks and chainplate on bulwark, Short sheet pad eye)
- 1 Wichard double chainplate on forward deck for removable forestay, 1 Dyneema halyard sheave with block for staysail
- Dual textile lifelines
- Cockpit sole, benches, platform with synthetic foam coating (light grey color) in place of the Iro-Deck
- White gel-coat, Aluminum grey hull decoration, white decoration film layer on cabins hull porthole

Winches - HARKEN Performa

- 2 H50.2 STP Harken Performa manual manoeuvre winches on the roof + 3 clutches on port and starboard roof
- 2 H60.2 STP Harken Performa manual genoa winches behind cockpit benches
- 2 H60.2 STP Harken Performa manual Spinnaker winches (For manoeuvring: main sail sheet, adjustment of Genoa sail carriage-staysail sheet - downhaul - foot of main sail + reef 1&2 - and for spinnaker sheets - spinnaker tack - barber hauler)
- 4 Aluminum Speed Grip winch handles
- Winch handle storage in dedicated space in rope bags

Other specificities of the PERFORMANCE version

- No windlass
- No bow roller
- No helm consoles for better access to the mainsail traveller on cockpit sole
- No side access gates
- No HiFi equipment (Fusion / Loudspeaker)
- No courtesy lighting on side decks
- Without cockpit table
- 1 Lithium battery replacing the AGM batteries (Weight saving: Approximately 110 kg / 242 lbs)
- 3 Lee cloth (Saloon & Aft cabins)
- Navicolor 3.5" screen

MOORING LINES - MOORING

- Polyester bowsprit (1,00m / 3'3") with integrated anchoring gear and bobstay with spinnaker chainplate (for Code 0 and asymmetric spinnaker) (First 44 version)
- Self-draining chain locker, Clench bolt, Hatch cover (First 44 version)
- Single roller stainless steel bow fitting (First 44 version)
- 12 V - 1 000 W vertical electrical windlass - Remote control in mooring locker (First 44 version)
- 6 Anodised aluminum mooring cleats (Length: 0,30m / 12")
- Stainless steel chafing plate

SAIL LOCKER

Access through piston-driven cover

- LED lighting

SAFETY ON DECK

- 1 Stainless steel open pulpit
- 2 Stainless steel aft pulpits with integrated fairlead
- 1 Stainless steel aft central pulpit (Height: 960mm / 3'2")
- 2 Stainless steel handrails on coachroof
- 1 Lifebuoy support bracket on aft pulpit
- Wooden flagstaff (1m / 3'3") with integrated support on pushpit
- Dual stainless steel lifelines and stainless steel stanchions (Height: 620mm / 2') - Side boarding gate on either side (First 44 version)
- Emergency ladder on pushpit

COCKPIT

- Self-draining cockpit
- Iro-Deck slatted (First 44 version)
- 2 Sail lockers below cockpit seating
- 1 Access hatch to tender garage
- 1 Diesel deck filler at the aft of the side deck
- 1 Shore power socket in port side storage
- 1 Water deck filler located on forward roof on side deck
- 1 Gas locker in the bottom of the cockpit
- Iro-Deck slatted cockpit benches (First 44 version)
- Iro-Deck slatted side helmsman's seat (First 44 version)
- Foldaway helmsman foot chock
- Black composite helm (diameter 900 mm/2'11") fixed on white lacquered aluminum pedestal
 - Steering gear at the helm station
 - Stainless steel steering chain transmission system
- 1 Emergency tiller
- 1 Steering compass
- Mechanical engine throttle and control panel on starboard
- 1 Cockpit shower with mixer tap in the tender garage
- 1 PPMA folding companionway door in the bottom of the cockpit - Sliding hatch made of PMMA
- Liferaft locker in front of the companionway (Usable dimensions: 0,93m x 0,59m x 0,33m / 3'1" x 1'11" x 1'1")
- Courtesy lighting (6 LED lighting points, warm white lighting) (First 44 version)

SWIM PLATFORM / AFT TRANSOM

- Fully opening transom, convertible to bathing platform (2,32m x 0,67m / 7'7" x 2'2")
- 1 Folding access step to the cockpit to starboard
- Manual opening
- Iro-Deck slatted swim deck (First 44 version)
- 1 Stainless steel removable bathing ladder (dedicated storage in starboard cockpit locker)

TENDER GARAGE

Accessible from the platform and from the cockpit

Can be used to house a Highfield Roll-Up type tender (2m / 6'7")

- 1 Touch-operated ceiling LEDs

INTERIOR

- Alpi teak woodwork and white lacquered wood on bulkheads
- Alpkord teak flooring
- Lounge Falcon 162 fabric interior upholstery
- Mattresses in the cabins (HR foam 35 kg/m³, thickness 120 mm/5")
- Beige padded ceilings

Standard version: 3 cabins + 2 heads



COMPANIONWAY

Headroom: 1,98m / 6'6"

- Saloon companionway with 5 suspended Alpkord teak non-slip steps, LED lighting below each step
- 1 Leather-covered stainless steel handrail (DK02 - chocolat color)

SALOON

Headroom: 1,95m / 6'5"

Port saloon

- Alpi teak saloon table with fixed top (can seat up to 6 diners)
- Face to face benches with large storages under seat
- Face to face saloon convertible into double berth as option

Starboard saloon

- Comfortable sofa facing the saloon:
 - seats with HR26 and HR30 foam
 - softness thanks to the finish with hollow fibres + padding
 - Storage under seating
- 1 230 V socket
- 1 Electrical panel to starboard incorporated into a high cabinet

- 2 T44 Opening deck hatches with mosquito screen/blinds
- Indirect LED lighting below the soft and the upper part of the portholes
- 1 Adjustable reading light
- Pillar with beige cover

CHART TABLE

to starboard from the companionway

- Long chart table with fiddles, storage under the lifting top
- High cabinet with storage (or, in option, navigation screen)
- 1 Adjustable reading light
- 1 dual USB port
- 1 230 V socket

GALLEY - PORT

Headroom: 1,92m / 6'4"

- L-shaped galley
- Corian Glacier White work top with moulded Apli teak beading
- 1 1 rectangular stainless steel sink - 1 Mixer tap with hot/cold water under pressure
- 1 Gas cooker 2 burners - Stainless steel/grill fitted on swivel joints (19L) - Stainless steel protection handrail - Stowage below the oven with drop-down door
- 1 Storage unit with 1 door and 1 internal drawer for cutlery
- 190L / 50 US Gal icebox, with top and front opening
- Fitted lockers and closed shelving
- 1 Bin (20L)
- 1 Opened compartment along the side of the hull
- 1 Opening portlight with curtains in the coachroof side window

OWNER'S CABIN

Headroom: 1,93m / 6'4"

- Central double bed (2,04m x 1,12m - 1,60m / 6'9" x 3'8" - 5'3")
- Padding along the hull and at headboard: Beige PVC

- 1 Bed access sideboard
- 1 Chair on each side of bed
- 1 Hanger closet, with incorporated LED lighting
- 2 Flexible and adjustable bedside lamps
- 1 T60 flush deck hatch with blind/mosquito net
- 1 Flush opening deck hatch (330mm x 140mm)
- 2 Portholes with rigid sliding blind
- 1 230V power socket to starboard
- 1 dual USB port outlet on each side of the bed
- LED indirect lighting + 2 overhead lights

1 PRIVATE HEAD

to port

Headroom: 1,92m / 6'4"

- 1 Shower with foldable perspex door
- 1 Manual toilet
- 1 64 L / 17 US Gal rigid holding tank
- Work top in Corian Glacier White
- 1 Integrated polyester basin - Mixer tap
- 1 Cabinet - Mirror
- Toilet accessories
- 1 Deck hatch with opaque film
- LED indirect lighting + Spot lighting

PORT AND STARBOARD AFT CABINS

Headroom: 1,94m / 6'4"

- 1 Double bed (2,04m x 1,38m / 6'8" x 4'6")
- 1 Hanging locker, 1 Cupboard with shelves, with incorporated LED lighting
- 1 Top-opening storage in front of the wardrobe
- 1 Opened compartment along the side of the hull
- 2 Flexible and adjustable reading lights
- 1 dual USB port
- 1 230 V socket
- 1 Porthole with rigid sliding blind
- 1 Opening window with below cockpit seat with pleated blind
- 1 Opening window on coaming with pleated blind

AFT STARBOARD HEAD COMPARTMENT

Headroom: 1,93m / 6'4"

Access through saloon

- Shower separated with a perspex door - 1 Mixer tap - White polyester shower base
- Work top in Corian Glacier White
- 1 Manual toilet
- 1 64 L / 17 US Gal rigid holding tank
- 1 Washbasin - 1 Mixer tap
- 1 Cabinet + Storage space under the basin
- 1 Mirror
- Toilet accessories
- 1 Opening porthole on coaming in side window, opaque film, mosquito screen
- LED indirect lighting + 1 overhead light

ENGINE

- Engine Yanmar Diesel:
 - 57 HP, Sail Drive, Common Rail (standard)
- Engine control at the starboard helm station - Control panel
- Engine compartment:
 - Soundproofing foam
 - Ventilation: 2 air intakes and 1 forced air outlets
- 1 Alternator (12V / 125Ah)
- 1 Rotomoulded diesel tank 200 L / 53 US Gal (under port aft berth)
 - Electronic gauge - Low level alarm - 1 Deck filler
- Filters: Seawater - Diesel - Water separator
- Foldable three-blade propeller
- 1 Engine access through companionway (opening with 2 gas struts)
- 2 Engine access through aft cabins

PLUMBING

- 1 Rotomoulded freshwater tank 330 L / 87 US Gal, under berth in forward cabin - 1 Deck filler
- Pressurised electric water pump - Expansion tank - Inline filter
- 40 L / 11 US Gal Electric water heater (engine use)
- 1 Rigid black water holding tank for each WC
- Electrical shower drain pumps
- 1 Electric bilge pump
- 1 Manual bilge pump

GAS

- 1 Box for 2 gas bottles in the anchor locker (Diameter: 0,39 x 0,39m / 1'3" x 1'3" - Height: 0,51m / 1'8")
- Regulator and safety tap
- Gas leak detector

SMART BOARD

"SEANAPPS" smart technology:

- For monitoring the boat's status and receiving alerts as well as maintenance advice via the associated mobile application.
- The type of information collected (GPS position, batteries, engine info, navigation data, etc.) varies according to the boat's configuration.



ELECTRICITY

- 12 V electrical panel (Breaker, Voltmeter, Water gauge, Fuel gauge, Battery warning, Fuel warning, Water warning) + Single USB port + Navicolor 2.4" screen (For First 44 version) / Navicolor 3.5" screen (For First 44 Performance version)
- 12V circuit
- 2 AGM service batteries - 100Ah (For First 44 version)
- 1 AGM engine battery - 50Ah
- Battery cut-off switch in the aft starboard cabin (under bed)
- 1 Battery charger (40Ah)
- 1 Power distributor
- 5 230V Sockets:
 - 1 in the forward cabin
 - 1 in the aft cabins
 - 1 in the saloon (Starboard)
 - 1 at chart table
 - 1 in galley
- 6 USB sockets:
 - 2 in the forward cabin
 - 1 in the aft cabins
 - 1 on the electrical panel
 - 1 at chart table
- 1 Shore power socket 230 V, in the port cockpit locker
- LED lighting:
 - Overhead lights
 - Reading lights
 - Indirect lighting
- LED navigation lights:
 - 1 Masthead light
 - 1 Steaming light
 - 1 Anchor light on masthead

MISCELLANEOUS ITEMS

- Smoke detector
- Cleaning kit: eco-friendly cleaning products kit

TRIM LEVEL & PACKS

TRIM LEVEL (First 44)

	CONFORT	LUXE
<ul style="list-style-type: none"> Coastal Pack (GARMIN) Windlass control in cockpit with chain counter HiFi: Fusion RA210 + 2 Interior loudspeakers & 2 Waterproof exterior speakers Induction charging station for smartphones at the chart table Cabins: Mosquito nets for opening portholes LED indirect lighting Navicolor 3.5" screen, Battery charge display IBS sensor 2 Additional ancillary AGM batteries 12 V 100 A 	<ul style="list-style-type: none"> ■ ■ ■ ■ ■ ■ ■ ■ 	<ul style="list-style-type: none"> ■ ■ ■ ■ ■ ■ ■ ■
<ul style="list-style-type: none"> Offshore Pack (GARMIN) 1 Solid wood cockpit table on stainless steel pedestal, 2 extension leaves, 1 opened central storage + Protective cover (Cadet Grey) Electrical engine control on the starboard console 		<ul style="list-style-type: none"> ■ ■ ■

ELECTRONICS PACKS: GARMIN

Garmin Packs (First 44)

	COASTAL (included in the Confort trim level)	OFFSHORE (included in the Luxe trim level)
<ul style="list-style-type: none"> Port and starboard helm stations: <ul style="list-style-type: none"> Steering console 1 12" GPS Map 1223 multi-function touchscreen (GPS, Chart plotter, Card reader - Bluechart G3 cartography included) Wind Sensor gWind Race - pole 1m / 3'3": Windvane, Anemometer Aimar DST810 Sensor (Log, Speedometer, Temperature) PC interface (GND10) Fixed 315i VHF at chart table, without AIS receiver function Windex Windvane Protective covers for helm & consoles (Charcoal Grey) 	<ul style="list-style-type: none"> ■ ■ ■ ■ ■ ■ ■ 	<ul style="list-style-type: none"> ■ ■ ■ ■ ■ ■ ■
<ul style="list-style-type: none"> Reactor 40 Pilot with GHC 50 control on port console (LS40 hydraulic arm) Wireless autopilot remote control GARMIN Quatix 7 connected watch 		<ul style="list-style-type: none"> ■ ■ ■

FASTNET PACK (implies pack Coastal or Offshore pack)

- 3 GNX120 7" mast screens + mast bracket + cover
- 800 AIS
- GHS11 VHF Wired handset at starboard helm station

Garmin Pack (First 44 Performance)

PERFORMANCE PACK (without console at helm station)

- 3 GNX120 7" mast screens + mast bracket + cover
- 800 AIS
- GARMIN Quatix 7 connected watch
- Wind Sensor gWind Race - pole 1m / 3'3": Windvane, Anemometer
- 24xd NMEA 2000 GPS aerial
- PC interface (GND10)
- Aimar DST810 Sensor (Log, Speedometer, Temperature)
- Fixed 315i VHF at chart table, without AIS receiver function
- GHS11 VHF Wired handset at starboard helm station
- Windex Windvane
- Protective covers for steering wheels (Charcoal Grey)

RIGGING PACKS

For First 44 version

DOWNWIND PACK (Compatible with the 3 masts)

- 2 HARKEN Black Magic blocks for spinnaker/code 0 sheet
- 1 HARKEN Black Magic block for spinnaker tack led back to the dedicated cleat in the cockpit
- 1 Dyneema halyard sheave with block for spinnaker or code 0
- Barber hauler (Chain plate on bulwark)

SELF-TACKING RIGGING PACK (Compatible with all masts and all rigging packs)

- Self-tacking jib hardware (sheet only) - 3 Blocks
- 1 Self-tacking jib track with traveller

SELF-TACKING STAYSAIL RIGGING PACK (Compatible with the 3 masts - requires the self-tacking rigging pack)

- 1 Wichard double chainplate on forward deck for removable forestay
- 1 Dyneema halyard sheave with block for staysail

ALUMINUM SAILS MAST PACK - NORTH SAILS

- Full-batten mainsail, 2 reefs (53 m²/570 sq/ft) and Genoa (50 m²/539 sq/ft or 53 m²/570 sq/ft depending on furler) North Sails NPL tour, laminated, dark grey
- Facnor travellers: 1 header traveller, 5 intermediate travellers, 5 batten travellers
- Charcoal Grey lazy bag

CARBON MAST SAILS PACK - NORTH SAILS

- Full-batten mainsail, 2 reefs (61 m²/657 sq/ft) and Genoa (56 m²/603 sq/ft) North Sails NPL tour, laminated, dark grey
- Harken travellers: 1 header traveller, 6 intermediate travellers, 5 batten travellers
- Charcoal Grey lazy bag

MOORING PACK

- Delta 20 kg/44 lbs anchor (galvanized steel)
- Chain (Diameter: 10mm / 3/8" - Length: 32m / 105')
- Line (Diameter: 18mm / 11/16" - Length: 45m / 147')
- 6 Fenders:
 - 4 XL (Diameter: 300mm / 12" - Length: 880mm / 2'11")
 - 2 L (Diameter: 250mm / 10" - Length: 700mm / 2'4")
- 4 Mooring lines (Diameter: 18mm / 11/16" - Length: 15m / 49'3")

Compatible with First 44 and First 44 Performance version

BLACK EDITION PACK

- 6 Black anodised aluminum mooring cleats (Length: 0,40m / 1'4")
- Black lacquered stainless steel pulpits, handrails, stanchions
- Textile lifelines with side boarding gates (First 44 Performance version: without side boarding gates)

OPTIONS

NAVIGATION ELECTRONICS: GARMIN

First 44

- Chart table: 12" GPS Map 1223 multi-function touchscreen
- 800 AIS
- Panoptix PS51-TH (Forward underwater vision)
- Phantom 18x radar
- GHS11VHF wired handset at port helm station

RIGGING - SAILS

For First 44 version

- Manual genoa furler below deck
- Code 0 with North Sails Xi 06 TF1,FX-4500 Facnor furler, dark grey laminated: 95m² / 1,022 sq/ft (for aluminum mast)
- Code 0 with North Sails Xi 06 TF1,FX-4500 Facnor furler, dark grey laminated: 105m² / 1,130 sq/ft (for carbon mast)

Compatible with First 44 and First 44 Performance version

- Black lacquered aluminum classical mast
- Carbon classical mast (+ 1,60m / 5'3", Weight saving: 75kg / 165 lbs) 2 Aft swept spreaders + Black lacquered aluminium Racing boom with LED lighting + Mainsail sheet track at bottom of cockpit
- Harken hydraulic unit (Compatible with the 3 masts): Hydraulic textile backstay on piston, 1 speed

WINCHES

First 44

- 1 Port electric H50.2 STAEH rigging winch, in lieu of standard
- 1 Electric manoeuvre winch to port H50.2 STAEH, in lieu of standard
- Upgrade for manual genoa winches H60.2 STA, replacing standard manual H50.2STA
- 2 Electric Harken (H60.2 STAEH) genoa sheet winches, replacing standard manual H50.2STA

First 44 Performance

- Upgrade: 2 Harken Performa (H60.2 STPEH) electric manoeuvre winches

HULL - DECK - COCKPIT

For First 44 version

- Pearl grey gel-coat (Hull & Bowsprit), hull decoration white pearl
- Metallic hull paint (Hull, Aft transom, Bowsprit)
- Iro-Deck slatted side decks
- LED lighting of spreaders, for anodized aluminium mast, black lacquered aluminium mast, carbon mast
- Electrically opening bathing platform, Control at steering station + Remote control
- Water ballast in the aft cabins (not compatible with full boat air conditioning and heating options)
- Roof solar panels (400 W)

Compatible with First 44 and First 44 Performance version

- Ballast Performance (Cast iron/Lead)
- Retractable bow thruster + 2 Dedicated batteries (50 Amps - 12V) - Control on starboard console
- White composite steering wheels
- Outboard engine bracket
- Polyester folding gangway (2,60m / 8'6")
- Electric inflator/deflator for tender and fenders (portable, battery-powered)
- Shore fresh water supply
- 1,20 m/3'11" carbon flagstaff (in lieu of standard)

COCKPIT COMFORT - First 44

- Outside cockpit upholstery with backrests. Filter foam 80 mm/3" thickness (Density: 60F + 20S).
 - Sunbrella Loop Sand
 - Dolce 51

OUTSIDE PROTECTIONS - First 44

- Sprayhood with LED lighting, Strataglass windows, Charcoal Grey
- Bimini Charcoal Grey (sprayhood option required)
- Sunshade for the cockpit, Charcoal Grey (compatible with all booms)

INTERIOR EQUIPMENT

AMBIANCE

- Interior upholstery according to colour chart: Fabrics, Leather, Nubuck, Ultraleather

DOMESTIC APPLIANCES

- 3 burners ENO Grand Large Gas cooker + Tempered glass cover on the hotplate

ON BOARD COMFORT EQUIPMENT

For First 44 version

- Berth in saloon (Electric saloon table pedestal + cushion matching the saloon upholstery for Lounge area use)
- 12V / 230V inverter - 2 000 VA
- 1 200Ah Lithium batteries to replace the AGM batteries - Weight saving: Approximately 110 kg / 242 lbs
The lithium batteries can be used in exactly the same way as the greater number of AGM batteries that they replace. This technology allows 100% of the battery capacity to be used compared with 75% for the AGM batteries. The engine battery is still AGM.
- Additional water tanks (200L / 53 US Gal), under aft starboard cabin berth
- Seawater electric pump, in galley
- TECMA electric fresh water/sea water WC in the owner's head
- Quiet Flush fresh water/seawater electric WC in the aft starboard head
- Spring mattress in the owner's cabin (thickness: 180mm / 7")

Compatible with First 44 and First 44 Performance version

- Air conditioning 16 000 BTU in saloon and forward cabin (+ Shore socket extension cord 15m / 49'3") - 32A
- 24 000 BTU air conditioning full boat (only for use via shore power supply) + Shore socket extension cord 15m / 49'3"
- Tableware - 6 people